जोधपुर नगर निगम, जोधपुर –दक्षिण

कमांक:-/विकास/तृतीय/ दक्षिण/2022-23/277

दिनांक:- 5/7/022

ः अल्पकालीन ई-निविदा सूचना ः

DLB2223WSOB10301

नगर निगम दक्षिण जोधपुर की और से निम्नलिखित कार्यो हेतु भारत सरकार एवं राज्य सरकार के विभिन्न विभागों / स्वायतशाषी / निगमों / बोर्डो / राजकीय उपक्रमों में पंजीकृत ए.०ए व ए. श्रेणी में पंजीकृत तथा नगर निगम जोधपुर में निर्धारित श्रेणी में पंजीकृत नियमानुसार योग्य संवेदको से निर्धारित प्रपत्र में ई—निविदाएं आमंत्रित की जाती है।

महत्वपूर्ण दिनांकों का विवरण

विवरण	दिनांक
ऑन लाईन निविदा फार्म जमा कराना प्रारम्भ होने की दिनांक व समय	13.7.022 /12,30 PM
	20.7.022 /12.30 PM
ऑन लाईन निविदा खोलने की तारीख	20,7,022 /3, copm
निविदा शुल्क / धरोहर राशि की मूल प्रति अधीक्षण अभियन्ता कार्यालय में जमा कराने की दिनांक व समयावधि	20,7,022 / 2. WPM

	जना करान का दिनाक व सनवावाव				4
कं. स.	कार्य का नाम	अनुमानित लागत (राशि लाखों मे)ं	धरोहर राशि	निविदा शुल्क	कार्य पूर्ण करने की अवधि
1	Development work in Brij Park at sector A Shastri Nagar, Jodhpur (NCAP)	17.17	34,340/-	500/-	6 माह
2	C.C. Road & Interlocking tile & other development work near matki circle to mahaveer nagar at near by road in Ward No. 76 NNJS (NCAP)	85.00	1,70,000/-	1000/-	6 माह
3	Development Work at B Road from Gol Building Cricle To children Park in city zone NNJS (NCAP)	90.00	1,80,000/-	1000/-	6 माह
4	Constuction of footpath and parking in ward No. 80 Shikargargh Army Gate to along nala	135.00	2,70,000/-	2000/-	6 माह
5	Sewer line and CC road Work at various Places in Ward No. 57	12.54	25,080/-	500/-	4 माह

निविदा की महत्वपूर्ण शर्ते निम्नानुसार है :-

- 1. निविदा प्रपत्रों को वेबसाईट http://eproc.rajasthan.gov.in से डाउनलोड किया जा सकता है। इन निविदाओं में भाग लेने वाले संवेदको को निविदा को इलेक्ट्रोनिक फॉरमेट में वेबसाईट http://eproc.rajasthan.gov.in पर जमा करानी होगी।
 - 2. निविदा की प्रकिया ऑन लाईन होगी।
 - 3. निविदा हेतु पात्र संवेदको की श्रेणी -

किसी भी सीमा तक रूपये 300.00 लाख तक रूपये 150.00 लाख तक रूपये 50.00 लाख तक रूपये 15.00 लाख तक

- एए श्रेणी, संवेदक
- ए, श्रेणी संवेदक
- बी, श्रेणी संवेदक
- सी, श्रेणी संवेदकडी, श्रेणी संवेदक

4. निविदा खोलने की तिथि को किसी कारणवंश यदि सम्पूर्ण निविदायें नहीं खोली जा सकती है, तो उसके अगले कार्य दिवस को शेष निविदायें खोलने का कार्य जारी रखा जावेगा। निविदा प्रकिया -

कार्य सडक पोटेशियल असेसमेंट

पोस्ट क्वालीफिकेशन

अन्य निर्माण कार्य

150 लाख से 500 लाख तक 100 लाख से 200 लाख तक

500 लाख से अधिक तक 200 लाख से अधिक तक

5. निविदादाता द्वारा निविदा शुल्क, धरोहर राशि एवं प्रकिया शुल्क हेतु निम्नलिखित राशि कि मूल प्रति जोधपुर नगर निगम कार्यालय में नियमानुसार निविदा खोले जाने के समय से पूर्व जमा करवाना आवश्यक है। निम्नलिखित डिमांड / बैंकर चैक शुल्क ऑनलाईन निविदा फार्म जमाने की अन्तिम तिथि से पूर्व का होना आवश्यक है।

क्रं.सं.	शुल्क वितरण	शुल्क	भुगतान का प्रकार	
1	निविदा शुल्क	उपरोक्तानुसार	डिमाण्ड ड्रॉफ्ट /	देय
		34.11	बैंकर चैक	आयुक्त
			विकर चक	जोधपुर नगर निगम दक्षिण
2	धरोहर राशि	उपरोक्तानुसार	D	
	000000000000000000000000000000000000000	o radali gant	डिमाण्ड ड्रॉफ्ट /	आयुक्त
3	ई–टेण्डरिंग प्रकिया	50 लाख एवं उपन	बैंकर चैक	जोधपुर नगर निगम दक्षिण
	शुल्क	50 लाख एव उपर	डिमाण्ड ड्रॉफ्ट/	MD RISL, JAIPUR
N .	3, 1	1000/-	बैंकर चैक	
		50 लाख से नीचे		x = 8
		500/-		9 99

- प्रदत दरें निविदा खोलने की दिनांक से 90 दिवसों तक निविदा स्वीकृति हेतु मान्य (Vaild) रहेगी। यदि निविदाकर्ता उस अवधि में अपनी निविदा अथवा शर्तों में किसी प्रकार का संशोधन करता है अथवा अपनी निविदा वापस ले लेता है, तो उसकी धरोहर राशि जब्त कर ली जावेगी।
- यदि संवेदक के नजदीकी रिश्तेदार (प्रथम रक्त सम्बन्धी व उनके पति / पत्नी) कार्य से संबंधित अधीनस्थ कार्यालय में खण्डीय लेखाकार अथवा सहायक अभियन्ता से लेकर अधीक्षण अभियन्ता स्तर का किसी भी स्तर पर पदस्थापित हो, तो उसके कार्य पर नियुक्त करने पर प्रतिबन्ध रहेगा।
- राज्य सरकार में किसी भी अभियांत्रिकी विभाग में किसी भी इंजीनियर अथवा इंजीनियर या प्रशासनिक कार्य पर नियुक्त राजपत्रित अधिकारी राज्य की अनुमति के बिना सेवा निवृति के 2 वर्ष तक संवेदक अथवा उसके कर्मचारी के रूप में कार्य नहीं कर सकेंगे। यदि संवेदक अथवा उसके कर्मचारियों मे कोई ऐसा व्यक्ति जिसने राज्य सरकार की उक्त लिखित अनुमति निविदा जमा कराने से पहले अथवा संवेदक के यहां से सेवायें लेने से पहले अनुमित नहीं ली है, तो अनुबन्ध रद्द किया जा सकेगा।
- 9. उक्त आईटम की दोष निवारण अवधि 3 वर्ष होगी।
- 10. निविदा में निविदादाताओं से अंतर राशि परफोरमेन्स सिक्यूरिटी के रूप में प्राप्त करने के पश्चात ही स्वीकृति निविदा का कार्यादेश दिया जायेगा।
- 11. किसी भी निविदा को स्वीकार करने एवं बिना कारण बताये निरस्त करने के समस्त अधिकार निम्नहस्ताक्षर कर्ता को रहेगा। RPWA 100 की समस्त शर्ते उस सीमा तक मान्य/लागु होगी जिस सीमा तक के राजस्थान लोक उपापन पारदर्शिता अधिनियम 2012 एवं नियम 2013 के विरोध में नहीं हो।
- 12. वित्त विभाग के आदेश संख्या एफ—(1)एफ.डी./जी.एफ. एण्ड ए.आर./2007 दिनांक 30.09.11 (सर्कुलर नं. 19/2011) के अनुसार 50.00 लाख रूपये तक की राशि के कार्यों के लिए 500/- व 50.00 लाख रूपये से अधिक राशि के कार्यों के लिए 1000/— रूपये की राशि निविदा शुल्क के अतिरिक्त देनी होगी जो डिमाण्ड ड्राफ्ट या बैंकर चैक के रूप में देय होगी। यह डिमाण्ड ड्राफ्ट या बैंकर चैक मैनजिंग डायरेक्ट, आर.आई.एस. एल. के पक्ष में व जयपुर में भुगतान योग्य होना चाहिए।
- 13. नेगोशिएशन की आवश्यकता होने पर ई—मेल व पत्र द्वारा डाक से सूचित किया जायेगा।

,14. ई-टेण्डरिंग के लिए निविदादाता हेतु निर्देश :-

- इन निविदाओं में दिलचस्पी लेने वाले निविदा दाता निविदा प्रपत्रो का इन्टरनेट साईट http://www.eproc.rajasthan.gov.in से देख / डाउनलोड कर सकते है।
- निविदाओं में भाग लेने वाले निविदादाताओं को इन्टरनेट साईट http://www.eproc.rajasthan.gov.in पर रिजस्टर करवाना होगा। ऑन लाईन निविदा में भाग लेने के लिए डिजिटल सार्टिफिकेट है इनफोरमेशन टेक्नोलॉजी एक्ट 2000 के तहत प्राप्त करना होगा जो इलेक्ट्रोनिक निविदा में साईन करने हेतु काम आयेगा। निविदादाता उपरोक्त डिजिटल सर्टिफिकेट सी.सी.ए. द्वारा स्वीकृत एजेन्सी से प्राप्त कर सकते है। जिन निविदादाताओं के पास पूर्व में वैध डिजिटल सर्टिफिकेट है, नया डिजिटल लेने की आवश्यकता नहीं है।
- निविदादाताओं को निविदा प्रपत्र इलेक्ट्रोनिक फार्मेट में उपरोक्त वेबसाइट पर डिजिटल साईन के साथ प्रस्तुत करना होगा। जिसके प्रस्ताव अकेले भौतिक फॉर्म में स्वीकार्य नहीं होगा।
- इलेक्ट्रोनिक निविदा प्रपत्रों को जमा कराने से पूर्व निविदादाता यह सुनिश्चित कर लेवे की निविदा प्रपत्रों से संबंधित सभी आवश्यक दस्तावेजों की स्केन कॉपी निविदा प्रपत्रों के साथ अटेच कर दी गयी है।
- कोई भी टेण्डर इलेक्ट्रोनिकली जमा कराने से किसी कारण से लेट हो जाता है तो उसका जिम्मेदार विभाग नहीं होगा।
- टेण्डर के प्रपत्रों में आवश्यक सभी सूचियों को सम्पूर्ण रूप से भरकर ऑन लाईन दर्ज करे।
- 15. निविदायें राजस्थान लोक उपापन पारदर्शिता अधिनियम 2012 एवं नियम 2013 के अन्तर्गत आमंत्रित की जाती है। उपर अंकित समस्त प्रावधान / बंधन उस सीमा तक ही लागु होंगे जिस सीमा तक दे उस बिन्दु में उल्लेखित अधिनियम एवं नियमों के विरुद्ध नहीं हो।
- 16. आयुक्त नगर निगम जोधपुर के आदेश कमांक 9836 दिनांक 07.02.2020 एंव 9975 दिनांक 14.07.2020 के अनुसार पंजीयन रिव्यू आदेश के तहत निविदा स्वीकार/अस्वीकार की जायेगी।
- 17. राजकीय अवकाश की स्थिति में अगले कार्य दिवस की तिथी मानी जायेगी।
- 18. श्रीमान् निदेशक, स्वायत्त शासन विभाग राजस्थान जयपुर के आदेश कमाक 144612—825 दिनांक 22.11.2021 की पालना में वित्त विभाग की अधिसूचना दिनांक 22.10.2021 अनुसार आर.टी.पी.पी. नियम 2013 में Additional Performance Security के लिए नियम 75 –ए के अनुसार Additional Performance Security जमा करवानी होगी।

(अरूण कुमार पुरोहित) R.A.S. आयुक्त जोधपुर नगर निगम दक्षिण

जोधपुर नगर निगम, जोधपुर-दक्षिण

कमांक:-/विकास/तृतीय/ दक्षिण/2022-23/*2नन*

दिनांक:- 5/7/022

ः अल्पकालीन ई-निविदा सूचना ःः

(यू.बी. संख्या... DLB2223WSOB10301

नगर निगम दक्षिण जोधपुर की और से विकास कार्यो हेतु ऑनलाईन निविदा आमंत्रित की जाती है, कार्यो की विस्तृत जानकारी एवं शर्तो इत्यादि वेबसाईट http://eproc.rajasthan.gov.in, sppp.raj.gov.in पर व जोधपुर नगर निगम दक्षिण की वेबसाईट urban.rajasthan.gov.in /mcjs देखी जा सकती है।

(सुश्री वनिता सेठ) महापौर जोधपुर नगर निगम—दक्षिण (अरूण कुमार पुरोहित) R.A.S. आयुक्त जोधपुर नगर निगम—दक्षिण

दिनांक:- 5/7/022

कमांक:- 278 के 285

प्रतिलिपि :- सूचनार्थ एवं आवश्यक कार्यवाही हेतु।

1. श्रीमान जिला कलेक्टर महोदय, जोधपुर।

2. निदेशक / अधीक्षण अभियन्ता, स्थानीय निकाय विभाग, जयपुर।

3. अधीक्षण अभियन्ता / अधिशाषी अभियन्ता, सा.नि.वि. / जोधपुर विकास प्राधिकरण जोधपुर।

4. वरिष्ठ लेखाधिकारी, जोधपुर नगर निगम दक्षिण।

5. राजस्थान संवाद, जयपुर को भेजकर लेख है कि निविदा सूचना एक राज्य स्तरीय एवं एक क्षेत्रीय स्तरीय समाचार पत्र में प्रकाशन हेतु भिजवाये एवंम् समाचार पत्र के नाम बाबत् ईन्टीमेशन मेल नगर निगम जोधपुर दक्षिण को भिजवाये।

6. श्री रामेश्वर गहलोत, प्रोग्रामर नगर निगम जोधपुर दक्षिण को भेजकर लेख है कि ई—निवदा सूचना urban.rajasthan.gov.in/mcjs एवं sppp.rajasthan.gov.in, पर अपलोड़ करें एवम् निविदा सूचना प्रकाशन हेत् राजस्थान संवाद जयपुर को मेल के माध्यम से भिजवायें।

7. सहायक अभियन्ता श्री भवानी सिंह को भेजकर लेख है कि कार्यों की जी—सारणी एवं ई—निविदा सूचना http://eproc.rajasthan.gov.in पर अपलोड करे।

सूचना पट्ट जोधपुर नगर निगम दक्षिण।

आयुर्क्त जोधपुर नगर निगम –दक्षिण

OFFICE OF THE MUNICIPAL CORPORATION, JODHPUR

G-SCHEDULE

Last Date of Sale :-

Earnest Money: Rs.

Date of Receipt :-

CR No. Dated.

Copy issued to M/s

Rate Based on RUIDP 2017

Name of Work - Development work at Brij park situated in A sector shastrinagar S No

S .No.	Particulars	Otre	T 11-22		
1	Dismantling of existing structures like culverts, bridges, retaining walls, CC road and other structure comprising of masonry, cement concrete, wood work, steel work, including T&P and scaffolding wherever necessary, sorting the dismantled material, disposal of unserviceable material and stacking the serviceable material with all lifts and lead of 50 metres as directed by Engineer.	Qty.	Unit	Rate	Amount
а	Lime Concrete, cement concrete grade M-10 (1:5:10) and below	103.50	cum	264.00	27204
b	Dismantling Stone Masonry Rubble stone masonry in cement mortar	20.00	cum	256.00	27324 5120
2	Providing and laying lean cement concrete 1:4:8 in Sub- base over a prepared sub-grade with coarse and fine aggregate conforming to IS: 383, the size of coarse aggregate not exceeding 25 mm, aggregate cement ratio not to exceed 15:1, aggregate gradation after blending to be as per table 600-1, cement content not to be less than 150 kg/ cum, optimum moisture content to be determined during trial length construction, concrete strength not to be less than 10 Mpa at 7 days, mixed in concrete mixer, laid manualy, compacted with surface vibrator, finishing and curing complete as per clause 601, 112 of MoRT&H specification including all material, labour, machinery, lighting, guarding and maintenance of diversion.	194.40	cum	2300.00	447120
3	Providing and fixing precast cement concrete M-20 grade (Using mechanical Concrete Mixer) kerb stone top and bottom width 115 and 165 mm respectively, 250 mm high on 150 mm thick PCC M-10 grade foundation as per design, including fixing at site as per clause 408 of MoRT&H Specification including all material, labour, machinery, lighting, guarding and maintenance of diversion.	1080.00	mtr	254.00	274320
4	Providing and fixing of 60mm thick precast cement concrete interlocking paver block casted with rubber moulds in approved reflective colour and design having minimun compressive strength of 300 kg/ sq cm. The CC paving blocks be laid on average 50mm thick bed of coarse sand and the joint is to be filled with fine sand. Laying procedure on compacted sub-base as defined. Complete job is to be executed as per the instruction of Engineer incharge. The rates to be inclusive of all lead & Lifts etc. complete as per specifications.	972.00	sqm	641.00	623052
	Random rubble masonry with hard stone in foundation and plinth : Cement mortar 1:6 (1 cement : 6 coarse sand)	11.25	cum	3190.00	35887.5
6	Pointing on stone work with cement mortar 1:3 (1 cement : 3 fine sand) : Flush/ Ruled pointing	300.00	sqm	141.00	42300
7	Finishing walls with water proofing cement paint of required shade New work (Two or more coats applied @ 3.84 kg/10 sqm).	1050.00	sqm	86.00	90300
8 i	Carriage of Materials by mechanical transport ncluding loading, unloading and stacking ::Earth 5 km	123.50	cum	165.00	20377.5

	Steel work welded in built up sections/ framed work including			κ.	-
	cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works.	1500.00	kg	87.50	131250
10	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :Two or more coats on new	300.00	sqm	69.00	20700
	work				1717751

- 1. सभी प्रकार के कर (टैक्स) संवेदक द्वारा ही वहन किये जायेगें।
- 2. कार्य स्थल पर श्रमिक व सामग्री की सुरक्षा की जिम्मेवारी संवेदक की होगी।
- 3.जी.सारणी में वर्णित कार्यों के अतिरिक्त व अधिक कार्य संवेदक द्वारा दी गई दरों के आधार पर
- 4.कार्य स्थल पर कार्य संम्बंधित सूचनाएं दर्शाने वाला बोर्ड संवेदक को स्वयं के स्तर पर लगाना
- 5.टंकण त्रुटी की अवस्था में सम्बन्धित रेट मान्य होगी।
- 6. कार्य करने से पुर्व एवं कार्य करने के पश्चात कार्य स्थल की फोटो/विडियोग्राफी सीडी आवश्यक
- 7. दोष निवारण अविधि नियमानुसार रहेगी ।
- दरें 4 माह तक मान्य रहेगी
- 9 सशर्त निविद्धा स्वीकार नहीं होगी ।

EXECUTIVE ENGINEER NAGAR NIGAM SOUTH JODHPUR.

the above work @	Above/below the "G" Schedu	le.
I/We hereby agree to do the above work @	. (Signature of	Contractor)

JODHPUR MUNICIPAL CORPORATION, SOUTH

Based on RUIDP BSR, 2022

G-SCHEDULE

NIT No.	202	Date	500	222
NII NO.	2.	Date	2111	JEC

Sr No.	(2)

Last Date of Sale :-

Earnest Money : Rs.

Date of Receipt :-

CR No. Dated.

Copy issued to M/s

Name of work: cc road, Interlocking tile and other development work near matki circle to mahaveer circle and nearby roads

S.No.	ltem	Qty.	Unit	Rate In Rs.	amount
	Earth work in excavation for roadway, including trimming bottom and side slopes in accordance with requirement of line, grades and cross sections, including disposal of surplus material with all lift and lead upto 1000 metre as per				
	MoRT&H specification clause 301. Dismantling of flexible pavements and disposal of dismantled materials up to a lead of 50 metres as directed by Engineer.	1040.00	Cum	214.00	222560.00
2	Bituminous courses	110.00	Cum	411.00	45210.00
	Granular courses	220.00	Cum	286.50	63030.00
3	Dismantling of existing structures like culverts, bridges, retaining walls, CC road and other structure comprising of masonry, cement concrete, wood work, steel work, including T&P and scaffolding wherever necessary, sorting the dismantled material, disposal of unserviceable material and stacking the serviceable material with all lifts and lead of 50 metres as directed by Engineer	220.00	,	200.00	
	Cement Concrete Grade M-15 and above and PCC blocks	453.75	cum	652.00	295845.00
	Lime Concrete, cement concrete grade M-10 (1:5:10) and below	453.75	cum	365.00	165618.75
4	Providing and laying lean cement concrete 1:4:8 in Subbase over a prepared sub-grade with coarse and fine aggregate conforming to IS: 383, the size of coarse aggregate not exceeding 25 mm,aggregate cement ratio not to exceed 15:1, aggregate gradation after blending to be as per table 600-1, cement content not to be less than 150 kg/cum, optimum moisture content to be determined during trial length construction, concrete strength not to be less than 10 Mpa at 7 days, mixed in concrete mixer, laid manualy,compacted with surface vibrator, finishing and curing complete as per clause 601, 112 of MoRT&H specification including all material,labour, machinery, lighting, guarding and maintenance of diversion				,
5	Providing and laying un-reinforced, plain cement concrete mix with Concrete Mixer & vibrator pavement over a prepared sub base with 43 grade cement, coarse and fine aggregate conforming to IS: 383, maximum size of coarse aggregate not exceeding 25 mm, mixed as per approved mix design, laid, spread, compacted and finished in a continuous operation including provision of contraction, expansion construction and longitudinal joints etc including all material labour, machinery, lighting, guarding and maintenance of diversion. 9.6.1 PCC M-20		Cum		2331000.00

and the joint is to be filled with fine sand. Laying procedure on compacted sub-base as defined. Complete job is to be executed as per the instruction of Engineer incharge. The rates to be inclusive of all lead & Lifts etc. complete as per specifications. Providing and fixing precast cement concrete M-20 grade (Using mechanical Concrete Mixer) kerb stone top and bottom width 115 and 165 mm respectively, 250 mm high on 150 mm thick PCC M-10 grade foundation as per design, including fixing at site as per clause 408 of MoRT&H Specification including all material, labour,machinery, lighting, guarding and maintenance of diversion Cement plastering including T&P, scaffolding, material and complete labpour, including cost of water, curing, racking of joints etc. with 20 mm cement plaster of mix :1:6 (1 cement : 6 fine/ coarse sand) Supplying and fixing soorsagar bhura or equialent ashlar sills limitel and dassa ,bearing ,bed and top surface made perfeenctly even jambs ,skirting steps etc. rough dressed upto 15 cm thick. Random rubble masonry with hard stone in foundation and plinth : Cement mortar 1:6 (1 cement : 6 coarse sand) Supplying & fixing 560mm dia SFRC manhole frame & cover as per IS : 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect as directed by the Engineer Carriage of Materials by mechanical transport including loading,unloading and stacking : 5 km Earth Sand, bazri, ballast, kankar Providing and fixing steps and Laying pour provided in the provided prov		in a	roviding and fixing of 60mm thick precast cement concrete interlocking paver block casted with rubber moulds in pproved reflective colour and design having minimun compressive strength of 300 kg/ sq cm. The CC paving blocks be laid on average 50mm thick bed of coarse sand				,
Providing and fixing precast cement concrete M-20 grade (Using mechanical Concrete Mixer) kerb stone top and bottom width 115 and 165 mm respectively, 250 mm high on 150 mm thick PCC M-10 grade foundation as per design, including fixing at site as per clause 408 of MoRT&H Specification including all material, labour,machinery, lighting, guarding and maintenance of diversion Cement plastering including T&P, scaffolding, material and complete labpour, including cost of water, curing, racking of joints etc. with 20 mm cement plaster of mix :1:6 (1 cement : 6 fine/ coarse sand) Supplying and fixing soorsagar bhura or equialent ashlar sills lintel and dassa bearing bed and top surface made perfeenctly even jambs ,skirting steps etc. rough dressed upto 15 cm thick. Random rubble masonry with hard stone in foundation and plinth: Cement mortar 1:6 (1 cement : 6 coarse sand) Supplying & fixing 560mm dia SFRC manhole frame & cover as per IS : 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect as directed by the Engineer Carriage of Materials by mechanical transport including loading,unloading and stacking : 5 km Earth 10 Sand, bazri, ballast, kankar	6	a 0	and the joint is to be filled with fine sand. Laying procedure on compacted sub-base as defined. Complete job is to be executed as per the instruction of Engineer incharge. The rates to be inclusive of all lead & Lifts etc. complete as per			727.00	2063600.00
Cement plastering including T&P, scaffolding, material and complete labpour, including cost of water, curing, racking of joints etc. with 20 mm cement plaster of mix :1:6 (1 cement : 6 fine/ coarse sand) Supplying and fixing soorsagar bhura or equialent ashlar sills lintel and dassa ,bearing ,bed and top surface made perfeenctly even jambs ,skirting steps etc. rough dressed upto 15 cm thick. Random rubble masonry with hard stone in foundation and plinth : Cement mortar 1:6 (1 cement : 6 coarse sand) Supplying & fixing 560mm dia SFRC manhole frame & cover as per IS : 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect as directed by the Engineer Carriage of Materials by mechanical transport including loading,unloading and stacking : 5 km Earth Sand, bazri, ballast, kankar			(Using mechanical Concrete Mixer) kerb stone top and bottom width 115 and 165 mm respectively, 250 mm high on 150 mm thick PCC M-10 grade foundation as per design, including fixing at site as per clause 408 of MoRT&H Specification including all material, labour,machinery,	2800.00	sqm	737.00	2003000.00
complete labpour, including cost of water, curing, racking of joints etc. with 20 mm cement plaster of mix :1:6 (1 cement : 6 fine/ coarse sand) Supplying and fixing soorsagar bhura or equialent ashlar sills lintel and dassa ,bearing ,bed and top surface made perfeenctly even jambs ,skirting steps etc. rough dressed upto 15 cm thick. Random rubble masonry with hard stone in foundation and plinth : Cement mortar 1:6 (1 cement : 6 coarse sand) Supplying & fixing 560mm dia SFRC manhole frame & cover as per IS : 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect as directed by the Engineer Carriage of Materials by mechanical transport including loading,unloading and stacking : 5 km Earth Sand, bazri, ballast, kankar				1480.00	mtr	312.50	462500.00
Supplying and fixing soorsagar bhura or equialent ashlar sills lintel and dassa ,bearing ,bed and top surface made perfeenctly even jambs ,skirting steps etc. rough dressed upto 15 cm thick. Random rubble masonry with hard stone in foundation and plinth : Cement mortar 1:6 (1 cement : 6 coarse sand) Supplying & fixing 560mm dia SFRC manhole frame & cover as per IS : 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect as directed by the Engineer Carriage of Materials by mechanical transport including loading unloading and stacking : 5 km Earth Sand, bazri, ballast, kankar		8	complete labpour, including cost of water, curing, racking of joints etc. with 20 mm cement plaster of mix :1:6 (1 cement : 6 fine/ coarse	540	Sqm.	264.00	5280.00
Random rubble masonry with hard stone in foundation and plinth: Cement mortar 1:6 (1 cement: 6 coarse sand) Supplying & fixing 560mm dia SFRC manhole frame & cover as per IS: 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect as directed by the Engineer Carriage of Materials by mechanical transport including loading,unloading and stacking: 5 km Earth Sand, bazri, ballast, kankar Random rubble masonry with hard stone in foundation and plinth: for coarse sand) 10.00 Cum. 4245.0 42450.00 42450.00 42450.00 10.00 Cum. 4245.0 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00 42450.00		9	Supplying and fixing soorsagar bhura or equialent ashlar sills lintel and dassa ,bearing ,bed and top surface made perfeenctly even jambs ,skirting steps etc. rough dressed upto 15 cm thick.	5.00	Cum.	4475.0	22375.00
as per IS: 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect as directed by the Engineer Carriage of Materials by mechanical transport including loading,unloading and stacking: 5 km Earth Sand, bazri, ballast, kankar as per IS: 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect as directed by the Engineer 25.00 Each 2685.00 67125.00 1040.00 cum 245.95 255788.00		10	Random rubble masonry with hard stone in foundation and plinth : Cement mortar 1:6 (1 cement : 6 coarse sand)	10.00	Cum.	4245.0	42450.00
12 loading,unloading and stacking : 5 km 1040.00 cum 245.95 255788.00 Earth 1040.00 cum 245.95 255788.00 Sand, bazri, ballast, kankar 907.50 cum 196.76 178559.70		1'	as per IS: 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect a	g as	Each	2685.00	67125.00
Sand, bazri, ballast, kankar 907.50 cum 196.76 178559.70		1	loading, unloading and stacking : 5 km				
ballast, kankar 907.50 cum 196.76 178559.70			Earth	1040.0	00 cum	245.95	255788.00
Total 8497341.45		_		907.5	0 cum	196.76	178559.70 8497341.4 5

- 1. सभी प्रकार के कर (टैक्स) संवेदक द्वारा ही वहन किये जायेगें।
- 2. कार्य स्थल पर श्रमिक व सामग्री की सुरक्षा की जिम्मेवारी संवेदक की होगी।
- 3.जी.सारणी में वर्णित कार्यों के अतिरिक्त व अधिक कार्य संवेदक द्वारा दी गई दरों के आधार पर करवाये जा सकेंगे।
- 4.कार्य स्थल पर कार्य संम्बंधित सूचनाएं दर्शाने वाला बोर्ड संवेदक को स्वयं के स्तर पर लगाना होगा।
- 5.टंकण त्रुटी की अवस्था में सम्बन्धित रेट मान्य होगी।
- 6. कार्य करने से पुर्व एवं कार्य करने के पश्चात कार्य स्थल की फोटो/विडियोग्राफी सीडी आवश्यक रूप से कार्यालय में जमा कराने होंगें।
- 7. दोष निवारण अंवधि नियमानुसार रहेगी ।
- 8. दरें 4 माह तक मान्य रहेगी
- 9 सशर्त निविदा स्वीकार नहीं होगी ।

EXECUTIVE ENGINEER
NAGAR NIGAM SOUTH JODHPUR.

I/We hereby agree to do the above work @ _____ Above/below the "G" Schedule.

OFFICE OF THE MUNICIPAL CORPORATION, JODHPUR

G-SCHEDULE

IIT No. 2.77	Date	5.7.0	22

Sr No. (3)

Last Date of Sale :-

Earnest Money: Rs.

Date of Receipt :-

CR No. Dated.

Copy issued to M/s

Rate Based on RUIDP 2022

Name of Work - Development work at b road from gol building circle to childern park

S	D. H.				
.No.	Particulars	Qty.	Unit	Rate	Amount
1	Dismantling of existing structures like culverts, bridges, retaining walls, CC road and other structure comprising of masonry, cement concrete, wood work, steel work, including T&P and scaffolding wherever necessary, sorting the dismantled material, disposal of unserviceable material and stacking the serviceable material with all lifts and lead of 50 metres as directed by Engineer.				
а	Lime Concrete, cement concrete grade M-10 (1:5:10) and below				
	For footpath and other cc work	120.00	cum	365.00	42000
2	Earth work in excavation for roadway, including trimming bottom and side slopes in accordance with requirement of line, grades and cross sections, including disposal of surplus material with all lift and lead upto 1000 metre as per MoRT&H specification clause 301. In all type of soil		Cum	303.00	43800
	For outer footpath work	1140.00	cum	214.00	243960
3	Providing and laying lean cement concrete 1:4:8 in Sub- base over a prepared sub-grade with coarse and fine aggregate conforming to IS: 383, the size of coarse aggregate not exceeding 25 mm, aggregate cement ratio not to exceed 15:1, aggregate gradation after blending to be as per table 600-1, cement content not to be less than 150 kg/ cum, optimum moisture content to be determined during trial length construction, concrete strength not to be less than 10 Mpa at 7 days, mixed in concrete mixer, laid manualy, compacted with surface vibrator, finishing and curing complete as per clause 601, 112 of MoRT&H specification including all material, labour, machinery, lighting, guarding and maintenance of diversion.	855.00	cum	2775.00	2372625
4	Providing and fixing precast cement concrete M-20 grade (Using mechanical Concrete Mixer) kerb stone top and bottom width 115 and 165 mm respectively, 250 mm high on 150 mm thick PCC M-10 grade foundation as per design, including fixing at site as per clause 408 of MoRT&H Specification including all material, labour, machinery, lighting, guarding and maintenance of diversion.				
_	For outer footpath work	2000.00	mtr	312.50	625000
5 t	Providing and fixing of 60mm thick precast cement concrete interlocking paver block casted with rubber moulds in approved reflective colour and design having minimun compressive strength of 300 kg/ sq cm. The CC paving blocks be laid on average 50mm thick bed of coarse sand and the joint is to be filled with fine sand. Laying procedure on compacted sub-base as defined. Complete ob is to be executed as per the instruction of Engineer incharge. The rates to be inclusive of all lead & Lifts etc. complete as per specifications.				323000
F	or outer footpath work	5700.00	sqm	737.00	4200900

-					
	Random rubble masonry with hard stone in foundation and plinth : Cement mortar 1:6 (1 cement : 6 coarse sand)	20.00	cum	4245.00	84900
\rightarrow	Carriage of Materials by mechanical transport including loading, unloading and stacking ::5 km				
_	Earth	120.00		-	
	Sand, bazri, ballast, kankar		cum	245.95	29514
12	Steel work welded in built up sections/ framed work including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works.	300.00	kg	196.76 117.50	299075.2 35250
13	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :Two or more coats on new work	250.00	sqm	97.50	24375
14	Supplying and stacking good earth at site of work Note: 1) Loading, unloading and carriage to be paid extra as per actual lead. 2) Earth measured in stacks will be reduced by 20% foe payment	21.60	cum	299.50	6469.2
15	Supply at site of work well decayed farm yard manure, from any available source, approved by the engineer in charge including screening and stacking	2.16 .	cum	671.00	1449.36
16	Spreading of sludge farm yard manure or/ and good earth in required thickness (cost of sludge, farm- yard manure or/and good earth to be paid for separately).0	21.60	cum	43.30	935.28
17	Supply and planting following species best quality container grown healthy trees of 3 mt. min. height, well established & free from disease at site in 1.20 m dia holes, 1.20 m deep dug in the ground, mixing the soil with decayed farm yard/sludge manure, backfilling the hole watering etc as required.		2		
	Gulmohar(Delonix regia)	10.00	EACH	1566.00	15660
	Jacaranda mimosifolia (Neelli Gulmohar)	10.00	EACH	1566.00	15660
	Plumeria alba (Champa) 3 M height minimum	10.00	EACH	1648.00	15660
	Bauhinia blakeana (Arckid)	10.00	EACH		16480
	Erythrina variegata (Lantern Tree)	10.00	EACH	1546.00 2391.00	15460
18	Providing, lowering, laying in trenches, aligning, fixing in position and jointing socketed rubber gasket type ISI marked uPVC pipes of Class III (6 Kg/sqcm) suitable for potable water with rubber ring joints (as per IS 4985-2000) of following outer dia with all accessories (excluding specials) complete including all material, labour, hydraulic testing and commissioning as per Technical Specifications and as per direction of Engineer. Note: E/w to be measured and paid separately.		2.011	2031.00	23910
	110 mm dia	200.00	mtr	300.50	60100
19	Edging with 2nd class bricks, laid dry lengthwise, including excavation, refilling, consolidation, with a hand packing and spreading nearly surplus earth within a lead of 50 metres.	150.00	metre	34.20	5130
37	Dismantling of flexible pavements and disposal of dismantled materials up to a lead of 50 metres as directed by Engineer.				
20		1		1	1
20	Bituminous courses	95.00	cum	411.00	39045

,					
	Providing and fixing M. S. tree guard 45 cm square in plan, height 1.20 metre above ground level and 0.40 metre below ground level. The vertical members shall consist of four nos angle iron of size 25x25x3 mm, 1.6 m long, one at each corner and 8 nos flat iron of size 25x3 mm, 1.2 m long. The vertical members shall be welded to 4 nos 25x6 mm M. S. flats placed horizontally around the vertical member of the cage. The tree guard shall be painted with two or more coats of synthetic enamel paint of approved brand and manufacture over a coat of primer, complete in all respect.	50.00	EACH	2096.00	104800
_	Total				8346150.54
		0340150.54			
1	स्थेनलेस स्टील पाइप से निर्मित बैन्चो की आपूर्ति विभिन्न सीनों में फिक्सिंग				
1	में X 0.55 मीटर चौड़ाई में सीट X 0.42 मीटर उंचाई में पीछे की सीट तथा बैन्च भू—तल से उंचाई 0.38 मीटर होगी। बैन्च स्टेनलेस स्टील के आयताकार पाईप (साईज 19 मि.मी. X 45 मि.मी. 20 गेज मोटाई) में फ्रेम तथा बैठने की सीट व पीछे बैक सीट हेतु स्टेनलेस स्टील के 24 नग वर्गाकार	65	Nos.	10000	650000
	Total				8996150 54

- 2. कार्य स्थल पर श्रमिक व सामग्री की सुरक्षा की जिम्मेवारी संवेदक की होगी।
- 3.जी.सारणी में वर्णित कार्यों के अतिरिक्त व अधिक कार्य संवेदक द्वारा दी गई दरों के आधार पर करवाये जा सकेंगे।
- 4.कार्य स्थल पर कार्य संम्बंधित सूचनाएं दर्शाने वाला बोर्ड संवेदक को स्वयं के स्तर पर लगाना होगा।
- इं.टंकण त्रुटी की अवस्था में सम्बन्धित रेट मान्य होगी।
- 6. कार्य करने से पुर्व एवं कार्य करने के पश्चात कार्य स्थल की फोटो / विडियोग्राफी सीडी आवश्यक रूप से कार्यालय में जमा कराने होंगें।
- 7. दोष निवारण अवधि नियमानुसार रहेगी ।
- 8. दरें 4 माह तक मान्य रहेगी
- 9 सशर्त निविदा स्वीकार नहीं होगी ।

EXECUTIVE ENGINEER
NAGAR NIGAM SOUTH JODHPUR.

I/We hereby agree to do the above work @ _____ Above/below the "G" Schedule.

JODHPUR MUNICIPAL CORPORATION, SOUTH

NIT No.277

Date 57,022

G-SCHEDULE

I act	Date	۰ŧ	0-1	_	
Last	Date	u	SAI	е.	-

Date of Receipt :-

Copy issued to M/s

Earnest	Money	:	Rs.			

CR No. Dated.

BASED ON RUIDP BSR, 2022 and PWD BSR 2018

Name of work: Construction of Foothpath and parking in ward no 80 shikargarh Army gate to along Nala

S.No.	Item	T 6:	1		
	Earth work in excavation for roadway, including trimering	Qty.	Unit	Rate In Rs	. amount
	bottom and side slopes in accordance with requirement of				
	mile, grades and cross sections including disposal of			77	
1	surplus material with all lift and lead upto 1000 metre as nor		8		-
	MoRT&H specification clause 301.		1.		
	* 1				
	Dismantling of flexible pavements and disposal of	2700.00	Cum	214.50	579150.00
	dismantled materials up to a lead of 50 metres as directed				2
2	by Engineer.		1		
_					
	Bituminous courses	20.00	Cum	411.00	9220.00
	Granular courses	40.00	Cum		8220.00
	Dismantling of existing structures like culverts, bridges,		Cuili	286.50	11460.00
	retaining walls, CC road and other structure comprising of	8			
	masonry, cement concrete, wood work, steel work, including				9
	T&P and scaffolding wherever necessary, sorting the				
	dismantled material, disposal of unserviceable material and stacking the serviceable material with all lifts and lead of 50				-
3	metres as directed by Engineer				
	, <u></u>				
	Cement Concrete Grade M-15 and above and PCC blocks				
	octrient concrete Grade ivi-15 and above and PCC blocks				
	Lime Concrete, coment concrete grade M 10 (4.5.40) and	110.00	cum	620.00	68200.00
	Lime Concrete, cement concrete grade M-10 (1:5:10) and below	440.00			
	Providing and laying lean cement concrete 1:4:8 in Sub-	110.00	cum	365.00	40150.00
	base over a prepared sub-grade with coarse and fine				
	aggregate conforming to IS: 383, the size of coarse		57		
	aggregate not exceeding 25 mm,aggregate cement ratio not	34 P		×	
	to exceed 15:1, aggregate gradation after blending to be as			1	
-	per table 600-1, cement content not to be less than 150 kg/		1	1	
4	cum, optimum moisture content to be determined during trial length construction, concrete strength not to be less than 10			i	
	Mpa at 7 days, mixed in concrete mixer, laid		1		
	manualy,compacted with surface vibrator, finishing and				
	curing complete as per clause 601, 112 of MoRT&H			×	
	specification including all material, labour, machinery,				-
	lighting, guarding and maintenance of diversion				
	*	950.00	Cum	2775.00	2636250.00
	Providing and laying un-reinforced, plain cement concrete				
	mix with Concrete Mixer & vibrator pavement over a				
	prepared sub base with 43 grade cement, coarse and fine				
	aggregate conforming to IS: 383, maximum size of coarse aggregate not exceeding 25 mm, mixed as per approved				
- In	mix design, laid, spread, compacted and finished in a			1	
	continuous operation including provision of contraction,				
- 1	expansion, construction and longitudinal joints etc including				
	all material, labour, machinery, lighting, guarding and				
	maintenance of diversion.				
	9.6.1 PCC M-20	50.00	cum	5420.00	271000 00
		30.00	cum	5420.00	271000.00

6	Providing and fixing of 60mm thick precast cement concrete interlocking paver block casted with rubber moulds in approved reflective colour and design having minimun compressive strength of 300 kg/ sq cm. The CC paving blocks be laid on average 50mm thick bed of coarse sand and the joint is to be filled with fine sand. Laying procedure on compacted sub-base as defined. Complete job is to be executed as per the instruction of Engineer incharge. The rates to be inclusive of all lead & Lifts etc. complete as per specifications.	9000.00	807	707.00	
7	(Using mechanical Concrete Mixer) kerb stone top and bottom width 115 and 165 mm respectively, 250 mm high on 150 mm thick PCC M-10 grade foundation as per design, including fixing at site as per clause 408 of MoRT&H Specification including all material, labour,machinery, lighting, guarding and maintenance of diversion		sqm	737.00	6633000.00
8	Cement plastering including T&P, scaffolding, material and complete labpour, including cost of water, curing, racking of joints etc. with 20 mm cement plaster of mix :1:6 (1 cement : 6 fine/ coarse sand)	2700.00	mtr	312.50	843750.00
9	Supplying and fixing soorsagar bhura or equialent ashlar sills lintel and dassa ,bearing ,bed and top surface made perfeenctly even jambs ,skirting steps etc. rough dressed upto 15 cm thick. HD 20	46.00	Sqm.	264.00	12144.00
10	Random rubble masonry with hard stone in foundation and plinth : Cement mortar 1:6 (1 cement : 6 coarse sand)		Cum.	4473.0	44730.00
11	Supplying & fixing 560mm dia SFRC manhole frame & cover as per IS: 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect as directed by the Engineer		Cum.	4245.0	127350.00
12	Providing and fixing MS iron tree guard 60 cm dia and 2 metre high above ground level formed of 4 Nos (25 x 6 mm) and 8 Nos (25 x 3 mm) vertical MS riveted to 3 Nos (25 x 6 mm) iron rings in two halves, bolted together with 8 mm dia and 30 mm long bolts including painting two coats with paint of approved brand over a coat of priming, complete in all respects.		Each	2685.00	69810.00
13	Supply and planting following species best quality container grown healthy trees of 2 mt. min. height, well established & free from disease at site in 0.90 m dia holes, 1 m deep dug in the ground, mixing the soil with decayed farm yard/sludge manure, backfilling the hole watering etc as required.Mangifera indica (Mango)		Each	1874.00	562200.00
14	Planting of trees by the road side (Avenue trees) in 0.60 m dia holes, 1 m deep dug in the ground, mixing the soil with decayed farm yard/sludge manure, planting the saplings, backfilling the trench, watering, fixing the tree guard and maintaining the plants for one year.		Each		341100.00
15	Providing at site, lowering & laying in trenches, aligning & jointing of PVC-U pipes (SN 8) as per IS 15328 (amended up to date) and as per specifications with rubber rings with socket and spigot joint, (EPDM/SBR) for all depths for pipe length as per drawing and specification including hydraulic field testing (including the cost and conveyance of water to site for testing) and commissioning etc complete as directed by Engineer. Note: E/w to be measured and paid separately. Length of pipe shall be measured in between the outer wall of two manholes / Inspection chambers. Pipe in the manhole/inspection chamber's wall shall deemed to be included in the item of manhole/inspection chamber shall not be payable. 160 mm Nominal Dia	101.00		1618.00	485400.00
16	Carriage of Materials by mechanical transport including loading, unloading and stacking : 5 km		metre	5 558.00	56358.00

Sand, bazri,	Sand, þazri, ballast, kankar					
--------------	---------------------------------	--	--	--	--	--

- 1. सभी प्रकार के कर (टैक्स) संवेदक द्वारा ही वहन किये जायेगें।
- 2. कार्य स्थल पर श्रमिक व सामग्री की सुरक्षा की जिम्मेवारी संवेदक की होगी।
- 3.जी.सारणी में वर्णित कार्यों के अतिरिक्त व अधिक कार्य संवेदक द्वारा दी गई दरों के आधार पर करवाये जा
- 4.कार्य स्थल पर कार्य संम्बंधित सूचनाएं दर्शाने वाला बोर्ड संवेदक को स्वयं के स्तर पर लगाना होगा।
- 5.टंकण त्रुटी की अवस्था में सम्बन्धित रेट मान्य होगी।
- 6. कार्य करने से पुर्व एवं कार्य करने के पश्चात कार्य स्थल की फोटो/विडियोग्राफी सीडी आवश्यक रूप से
- 7. दोष निवारण अवधि नियमानुसार रहेगी ।
- 8. दरें 4 माह तक मान्य रहेगी
- 9 सशर्त निविदा स्वीकार नहीं होगी ।

	EXECUTIVE ENGINEER
NAGA	R NIGAM SOUTH JODHPUR.

I/We hereby agree to do the above work @	Above/below the "G" Schedule
Tive hereby agree to do the above work as	Above/below the G benedule

(Signature of Contractor)

OFFICE OF THE MUNICIPAL CORPORATION, JODHPUR

G-SCHEDULE

NIT No. 277 Date 57,022

Sr No. (5)

Last Date of Sale :-

Date of Receipt :-

Earnest Money: Rs.

CR No. Dated.

Copy issued to M/s

Rate Based on RUIDP 2017

Name of Work - Sewer line and cc road work at various places in ward no. 57

S .No.	Particulars	Qty.	Unit	Rate	Amount in Rs
1	Earth work for Sewer line and Manhole in excavation in foundation, trenches manholes, road side chambers etc. including dressing of sides and ramming of bottoms, including getting out the excavated material, refilling after laying pipe/ foundation and disposal of surplus excavated material at a lead upto 50m suitable site as per direction of Engineer for following depths, below natural ground / Road top level including allowances for any additional excavation beyond the drawings (measurement for payment to be as per standard drawings), re-handling of material/earth to complete the task. In all types soils/ saturated soil such as moorum, sand, sandy silt, clay, black cotton soil, kankar, etc. Depth upto 1.5 m	270.00	cum	197.00	53190
2	Providing granular bedding having width = outer dia of pipe (Bc) + 500mm, thickness below pipe = 0.25Bc or 100mm (whichever is higher) and haunching = 0.5Bc, with graded hard crusher broken stone of 100% passing through 20mm sheive, 20 to 50 % passing through 10mm sheive and 100 % retain on 6.3mm sheive, laying in layers of thickness 10/15cm including ramming, consolidation etc complete for all type of pipes of following sizes as per drawing and or as directed by Engineer. 250 mm internal diameter	100.00	metre	149.00	14900
3	Providing at site, lowering & laying in trenches, aligning & jointing of RCC pipes NP4 class (with s/s ends) IS: 458 - 2003 (amended up to date) marked and pipes from 300 mm and upto 1800 mm manufactured through vertical casting process at all depths with Rubber gaskets (EPDM/SBR) for sewer lines as per IS: 5382 (including cost of Rubber gaskets, lubricants) as per drawing, sectional hydro testing of the sewer pipe line (including cost and conveyance of water to site for testing) etc., complete as per specification and / or as directed by Engineer. Note: E/w to be measured and paid separately 250 mm internal diameter	120.00	metre	804.00	96480

1	Providing and constructing of RR stone masonry circular				150
	upto 1.65m having 300mm thick RR stone masonry wall in cement sand mortar 1:4, including concreting PCC M-10 grade (1:4:8) for 225mm thick foundation including curing compaction and form work etc complete, PCC M15 for benching and channel portion, RCC M20 for 200mm thick cover slab including reinforcement, PCC M20 for fixing the manhole frame and cover using stone aggregate 20mm nominal size, 20mm thick inside and outside plaster in C. M. 1:3, inside plaster finished with floating coat of neat cement, vata in CM1:1 around pipe entering and leaving the manhole and also at the junction of masonry and concrete slab, providing and fixing of SFRC foot steps of approved make at every 0.30m height fixed in CM 1:3, supplying and fixing heavy duty SFRC manhole frame and cover as per IS 12592 (Part I and II) having clear opening of 560mm, including refilling of Jhiri, including curing, watering, ramming, hydro testing of manhole, conveyance & cost of water, and dewatering complete as directed by the Engineer. Note:- Excavation of earth work and road cutting for manhole will be measured and paid separately. Manhole	4.00	each manhole	12500.0	50000
5	for depth beyond 0.90 m and upto 1.65 m with RR stone masonary including 20mm plaster inside and outside as per drawing and direction of Engineer.		metre	6430.00	25720
6	Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering - All work upto plinth level :1:4:8 (1 Cement : 4 fine/ coarse sand : 8 graded stone aggregate 40 mm nominal size).	3.27	cum	3360.00	10977.12
7	Random rubble masonry with hard stone in foundation and plinth :Cement mortar 1:6 (1 cement : 6 coarse sand)	16.42	cum	3190.00	52367.04
8	Cement plastering including T&P, scaffolding, material and complete labpour, including cost of water, curing, racking of joints etc. with 15 mm cement plaster on the rough side of single or half brick wall of mix: 1:6 (1 cement: 6 fine/coarse sand)	28.80	sqm	161.00	4636.8
9	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded 20mm nominal size stone aggregate) finished with a floating coat of neat cement including cement slurry, but excluding the cost of nosing of steps etc. complete. 75mm thick	4.32	. sqm	548.00	2367.36
10	Supplying & fixing 560mm dia SFRC manhole frame & cover as per IS: 12592-2002 in existing manholes including grouting the frame in PCC M-15 complete in all respect as directed by the Engineer. HD-20	11.00	each	2400.00	26400
11	Dismantling of existing structures like culverts, bridges, retainingb walls, CC road and other structure comprising of masonry, cement concrete, wood work, steel work, including T&P and scaffolding wherever necessary, sorting the dismantled material, disposal of unserviceable material and stacking the serviceable material with all lifts and lead of 50 metres as directed by Engineer. Lime Concrete, cement concrete grade M-10 (1:5:10) and below	48.00	cum	264.00	12672
12	Providing at site, lowering & laying in trenches, aligning & jointing of PVC-U pipes (SN 8) as per IS 15328 (amended up to date) and as per specifications with rubber rings with socket and spigot joint, (EPDM/SBR) for all depths for pipe length as per drawing and specification including hydraulic field testing (including the cost and conveyance of water to site for testing) and commissioning etc complete as directed by Engineer. Note: E/w to be measured and paid separately. 110 mm Nominal Dia	15.00	metre	244.00	3660

13	poviding and laying lean cement concrete 1:4:8 in Sub-base over a prepared sub-grade with coarse and fine aggregate conforming to IS: 383, the size of coarse aggregate not exceeding 25 mm, aggregate cement ratio not to exceed 15:1, aggregate gradation after blending to be as per table 600-1, cement content not to be less than 150 kg/ cum, optimum moisture content to be determined during trial length construction, concrete strength not to be less than 10 Mpa at 7 days, mixed in concrete mixer, laid manualy, compacted with surface vibrator, finishing and curing complete as per clause 601, 112 of MoRT&H specification including all material, labour, machinery, lighting, guarding and maintenance of diversion	120.00	Cum	2300.00	276000
14	Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering - All work upto plinth level: 1:1½:3 (1 Cement: 1½ coarse sand: 3 graded stone aggregate 20 mm nominal size).	120.00	Cum	4700.00	564000
15	Supplying and fixing soorsagar bhura or equialent ashlar sills lintel and dassa ,bearing ,bed and top surface made perfeenctly even jambs ,skirting steps etc. rough dressed upto 15 cm thick.	0.43	Cum.	4475.0	1933.2
16	Carriage of Materials by mechanical transport including loading unloading and stacking : 5 km	80.00	Cum	165.00	13200
	Total G-schedule				1208503.52
-	H schedule item				
1	Finishing with floater	1200	sqm	38	45600
	Total G-and H schedule				1254103.52

सभी प्रकार के कर (टैक्स) संवेदक द्वारा ही वहन किये जायेगें।

- 2. कार्य स्थल पर श्रमिक व सामग्री की सुरक्षा की जिम्मेवारी संवेदक की होगी।
- 3.जी.सारणी में वर्णित कार्यों के अतिरिक्त व अधिक कार्य संवेदक द्वारा दी गई दरों के आधार पर
- 4.कार्य स्थल पर कार्य संम्बंधित सूचनाएं दर्शाने वाला बोर्ड संवेदक को स्वयं के स्तर पर लगाना होगा।
- उंकण त्रुटी की अवस्था में सम्बन्धित रेट मान्य होगी।
- 6. कार्य करने से पुर्व एवं कार्य करने के पश्चात कार्य स्थल की फोटो/विडियोग्राफी सीडी आवश्यक
- 7. दोष निवारण अवधि नियमानुसार रहेगी ।
- 8. दरें 4 माह तक मान्य रहेगी
- 9 सशर्त निविदा स्वीकार नहीं होगी ।

EXECUTIVE ENGINEER
NAGAR NIGAM SOUTH JODHPUR.

I/We hereby agree to do the above work @	Above/below the "G" Schedule.
	(Signature of Contracto